

SB-12 METALBOND

Page Number: 1/6
Version Number: 5
Revision Date: 10/29/12

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name: SB-12 METALBOND

Company Name: SUREBOND
3925 Stern Avenue
St. Charles, IL 60174
Phone: (877) 843-1818

Emergency Phone (24 hour): CHEMTREC
(800) 424-9300

Chemtrec (outside USA): (703) 527-3887

SECTION 2 - HAZARDS IDENTIFICATION

Routes of Entry: Entry through inhalation and skin most likely.

Effects of Exposure:

Eyes: Can cause irritation, redness, tearing and blurred vision.

Skin: Prolonged or repeated contact can cause moderate irritation, drying of the skin and dermatitis.

Inhalation: Excessive inhalation of vapors can cause respiratory irritation, headache, drowsiness and fatigue. High concentrations of vapors are anesthetic and may cause central nervous system effects such as dizziness.

Ingestion: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

NFPA Hazard Codes: Health: 1 Fire: 3 Reactivity: 0 PPE: B

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient Name	CAS Number	Percent	TSCA
Light Aliphatic Naphtha	64742-89-8	10 - 15	Y
Toluene	108-88-3	5 - 10	Y
n-Hexane	110-54-3	5 - 10	Y
Ethanol	64-17-5	< 5.0	Y

Notes: Remaining ingredients are not considered OSHA hazardous.

SECTION 4 - FIRST AID MEASURES

Eyes: Flush eyes gently with water for at least 15 minutes lifting eyelids occasionally; get prompt medical attention.

Skin: Wash thoroughly with soap and water; apply a mild skin cream. Remove contaminated clothing.

Inhalation: Move affected person to fresh air; if breathing is difficult, administer oxygen; if breathing has stopped, give artificial respiration. Get medical attention.

Ingestion: DO NOT INDUCE VOMITING. Get immediate medical attention.

SB-12 METALBOND

Page Number: 2/6
Version Number: 5
Revision Date: 10/29/12

SECTION 5 - FIRE FIGHTING MEASURES (Flash, UEL, LEL for solvent only)

Flammability Class:	I B
Flash Point:	0° F - 60° F (-17.78° C - 15.56° C) Tag Closed Cup
Explosive Range (LEL/UEL):	LEL: 1.0% UEL: 6.5%
Extinguishing Media:	Carbon dioxide, dry chemical, foam. Use water fog to cool material in vicinity of fire.
Special Fire-fighting Procedures:	Use self-contained breathing apparatus with full facepiece operated in pressure demand with full protective equipment.
Unusual Fire and Explosion Hazards:	Any closed container may rupture when exposed to extreme heat. Solvent vapors are heavier than air and travel along the ground. Vapors given off are flammable and may be ignited in air explosively.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Steps to be Taken in Case of Spill:	Eliminate all ignition sources. Ventilate confined areas. (Open windows and doors). Wear appropriate protective clothing. Cover with absorbent. Scoop into sealable safety container.
--	---

SECTION 7 - HANDLING AND STORAGE

Handling and Storage Precautions:

- Keep away from heat, spark and flame.
- Keep out of reach of children.
- Keep container closed while not in use.
- Do not cut or burn receptacles that have contained a solvent based product. Do not reuse this container.
- Use only in a well ventilated area.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits:

	ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
Light Aliphatic Naphtha	400.00 PPM	N/Est	N/Est	1000.00 PPM	500.00 PPM
Toluene	100.00 PPM	N/Est	150.00 PPM	150.00 PPM	150.00 PPM

SB-12 METALBOND

Page Number: 3/6
Version Number: 5
Revision Date: 10/29/12

n-Hexane	50.00 PPM	N/Est	N/Est	N/Est	50.00 PPM
Ethanol	1000.00 PPM	N/Est	N/Est	N/Est	1000.00 PPM

Ventilation: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV. Ventilate during application and curing of this product.

Personal Protective Equipment:

Respiratory Protection: If TLV of the product is exceeded, a NIOSH/MSHA jointly approved air supply respirator is advised in the absence of proper ventilation. OSHA regulations also permit the use of other types of NIOSH/MSHA respirators under specified conditions. (See your safety equipment supplier for more information).

Protective Clothing: Rubber gloves should be worn where skin contact is likely. Wear impervious clothing and shoes.

Eye Protection: Chemical goggles or safety glasses should be worn.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form:	Non-sag mastic
Odor:	Slight, hydrocarbon
Solubility (in water):	Insoluble in water
pH Value, +/- .3:	N/A
Boiling Range:	160° F - 230° F (71.11° C - 110° C)
Vapor Pressure (mmHg):	155 @ 68° F (20° C)
Evaporation Rate:	4.8 times faster than n-Butyl Acetate
Vapor Density:	Heavier than air
% Volatile, Weight:	Approx. 34.%
% Volatile, Volume:	Approx. 45.%
Specific Gravity:	1.09266
VOC (less H ₂ O or exempt):	< 370 g/l (34%)

Note: Boil range, evaporation rate, vapor density and pressure for solvent only.

SECTION 10 - STABILITY AND REACTIVITY

Stability: This product is stable.

Hazardous Polymerization: Hazardous polymerization will not occur.

Incompatibility: Keep away from strong oxidizing agents.

Conditions to Avoid: Keep away from heat, spark, open flames and any ignition source.

Hazardous Decomposition Products: Will produce fumes and smoke containing carbon monoxide and dioxide under fire conditions.

SB-12 METALBOND

Page Number: 4/6
Version Number: 5
Revision Date: 10/29/12

SECTION 11 - TOXICOLOGICAL INFORMATION

Carcinogenicity: NTP? N/E | IARC Monographs? N/E | OSHA? NO

Chronic Hazards

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain, nervous system, liver or kidney damage and cardiac arrhythmia. INTENTIONAL misuse of this product by deliberately inhaling its vapors may be harmful or fatal.

N-HEXANE can cause peripheral neuropathy (arm and leg damage) and central nervous system damage. Prolonged and repeated exposure has been suggested as a cause of the following effects in lab animals: liver and reproductive abnormalities, kidney, spleen, lung or eye damage.

May aggravate pre-existing disorders of these organs in humans.

May be harmful if absorbed through skin.

Repeated overexposure to TOLUENE may cause liver damage.

Toluene has been found to cause kidney, lung and spleen damage in laboratory animals.

SECTION 12 - ECOLOGICAL INFORMATION

No data available.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of following local, state, and federal regulations.

SECTION 14 - TRANSPORT INFORMATION

Ground Transport (DOT) - Domestic

Units less than 5 L (1.3 gallons liquid) i.e. 10 oz., 28 oz., 1 gal.

Proper Shipping Name: CONSUMER COMMODITY
Classification: ORM-D
DOT Label Required: ORM-D
Shipping Document: CONSUMER COMMODITY, ORM-D
ERG Code: 171

Units GREATER than 5 L i.e. 5 gal. pail

Proper Shipping Name: ADHESIVE
Classification: CLASS 3
DOT Label Required: Flammable Liquid, UN1133, Class 3
Shipping Document: ADHESIVE, 3, UN1133, PGIII, for 50 gal. drum use PG II
ERG Code: 128

SB-12 METALBOND

Page Number: 5/6
Version Number: 5
Revision Date: 10/29/12

Air Transport (DOT) - Domestic

Units less than 5 L (1.3 gallons liquid) i.e. 10 oz., 28 oz., 1 gal.

Proper Shipping Name: CONSUMER COMMODITY
Classification: ORM-D
DOT Label Required: ORM-D-AIR
Shipping Document: Consumer Commodity, ORM-D
ERG Code: 171

Units GREATER than 5 L i.e. 5 gal. pail

Proper Shipping Name: ADHESIVE
Classification: Class
DOT Label Required: Flammable Liquid, UN 1133, Class 3
Shipping Document: ADHESIVE, 3, UN1133, PG III, for 50 gal. drum use PG II
ERG Code: 128

Air Transport (IATA) - International

Units less than 5 L (1.3 gallons liquid) i.e. 10 oz., 28 oz., 1 gal.

Proper Shipping Name: CONSUMER COMMODITY
Classification: class 9
Label Required: ID8000
Shipping Document: Consumer Commodity, 9, ID8000
ERG Code: 9L

Units GREATER than 5 L i.e. 5 gal. pail, 50 gal. drum

Proper Shipping Name: ADHESIVE
Classification: Class 3
Label Required: Flammable Liquid, UN 1133, Class 3
Shipping Document: ADHESIVE, 3, UN1133, PGIII, for 50 gal. drum use PG II
ERG Code: 3L

Marine - Ocean Transport (IMDG)

Units less than 5 L (1.3 gallons liquid) i.e. 10 oz., 28 oz., 1 gal.

Proper Shipping Name: ADHESIVE
Classification: Class 3
Label Required: Flammable Liquid, UN1133, Class 3, Ltd. Qty.
(on Ocean container only, not required on cartons)
Shipping Document: ADHESIVE, 3, UN1133, PG III, LTD.QTY.
EMS Code: F-E, S-D