

SB - 130 NON-FLAMMABLE METAL SEALANT

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Page Number: 1/7
Revision Date: 11/30/2015

Product Name: SB-130 NON-FLAMMABLE METAL SEALANT

Company Name: SUREBOND
3925 Stern Avenue
St. Charles, IL 60174
Phone: (877) 843-1818

Emergency Phone (24 hour): CHEMTREC
(800) 424-9300

Chemtrec (outside USA): (703) 527-3887

SECTION 2 - HAZARDS IDENTIFICATION

GHS Classification: Eye irritation – Category 2B
Skin irritation – Category 2
Skin sensitization – Category 1B
Flammable liquids – Category 3

GHS LABEL ELEMENTS:

Hazard symbols:



GHS02



GHS07

Signal word:

Warning

Hazard statements: Flammable liquid and vapor
Causes skin irritation
May cause an allergic skin reaction
Causes eye irritation

PRECAUTIONARY STATEMENTS:

Prevention:

- Do not handle until all safety precautions have been read and understood.
- Keep away from heat/sparks/open flames/hot surface. No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Avoid breathing dust, fume or vapors.
- Do not get in eyes, on skin or on clothing.
- Wash hands and other skin areas thoroughly after handling
- Wear protective gloves/protective clothing/eye protection/face protection.

SB - 130 NON-FLAMMABLE METAL SEALANT

Page Number: 2/7

Revision Date: 11/30/2015

Response:

- **If on skin:** Wash with plenty of soap and water. If skin irritation or rash occurs, get medical attention.
- **If in eyes:** Rinse with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
- **If exposed or concerned:** Get medical advice/attention.
- **Specific treatment:** Seek immediate medical advice. Refer to product label and Section 4 of this SDS.
- **If eye irritation persists:** Get medical advice/attention.
- Take off contaminated clothing and wash it before reuse.
- In case of fire: Use dry chemical/water fog/foam to extinguish.

Storage: Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents and container in accordance with applicable local, regional, national and international regulations.

Other hazards: None known

Supplemental information: 80% of the mixture consists of component(s) of unknown acute toxicity.

CLASSIFICATION SYSTEM:

NFPA Ratings (scale 0 - 4)



Health = 2

Flammability = 2

Reactivity = 0

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient Name	CAS Number	Percent
Methyl Tri(methylethylketoxime)silane	22984-54-9	2.0 - 7.0
Amorphous Silica	7631-86-9	5.0 – 10.0
Octamethylcyclotetrasiloxane	556-67-2	0.1 – 1.0
Mineral Spirits	64742-88-7	1.0 – 5.0

Note: There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to the health or the environment and hence require reporting in this section.

SECTION 4 - FIRST AID MEASURES

Eye contact: Flush with copious quantities of lukewarm water for at least 15 minutes. Do not attempt to physically remove the solids or gums from the eye. Seek medical attention immediately if irritation persists.

Skin contact: Remove contaminated clothing. Wash thoroughly with warm water and non-abrasive soap. Seek medical attention if you feel ill or a reaction develops.

Inhalation: Remove to fresh air and provide water. Seek medical attention if you feel ill or a reaction develops.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention.

Most important symptoms/effects, acute and delayed: None known.

Indication of immediate medical attention and special treatment needed: Provide general supportive measures and treat symptomatically.

SECTION 5 - FIRE FIGHTING MEASURES (Flash, UEL, LEL for solvent only)

Suitable extinguishing media: Carbon dioxide, dry chemical, water fog or foam. Water can be used to cool fire exposed containers.

SB - 130 NON-FLAMMABLE METAL SEALANT

Unsuitable extinguishing media: None known.

Page Number: 3/7

Specific hazards arising from the chemical: Exposure to combustion products such as carbon oxides, silicone oxides and formaldehyde may be hazard to health.

Revision Date: 11/30/2015

Special protective equipment and precautions for fire fighters: Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Follow safe handling advice and personal protective equipment recommendations in Section 8.

Environment precautions: Discharged into the environment must be avoided. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up: Restrict access to the area of the spill. Provide ventilation, NIOSH/MHSA approved respirator and protective clothing. Scrape up sealant and place in container for disposal. Clean area as appropriate since silicone materials can represent a slip hazard. Cleaning may require steam, solvents or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur. Local, state, provincial, federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup.

SECTION 7 - HANDLING AND STORAGE

Precautions for safe handling: Handle in accordance with good industrial hygiene and safety practice. Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage, including any incompatibilities: Store in an adequately ventilated area under dry conditions between 50°F (10°C) to 77°F (25°C) and keep container tightly sealed when not in use. Do not store with strong oxidizing agents.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredient	CAS No.	Value Type (form of exposure)	Control parameters/ Permissible concentration	Basis
Amorphous Silica	7631-86-9	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m ³ /%SiO ₂ (Silica)	OSHA Z-3
		TWA	6 mg/m ³ (Silica)	NIOSH REL
Octamethylcyclotetrasiloxane	556-67-2	TWA	10 ppm	OSHA PEL
		TWA	10 ppm	ACGIH TLV
		STEL	15 ppm	ACGIH TLV
Mineral Spirits	64742-88-7	TWA	100 ppm	ACGIH TLV

Hazardous components without workplace control parameters: Methyl Tri(methylethylketoxime)silane (CAS# 22984-54-9)

Occupational exposure limits of decomposition products:

Ingredient	CAS No.	Value Type (form of exposure)	Control parameters/ Permissible concentration	Basis
Methyl Ethyl Ketoxime	96-29-7	TWA	10 ppm	DCC OEL
	Further information: Skin sensitization			
		TWA	10 ppm	US WEEL

SB - 130 NON-FLAMMABLE METAL SEALANT

Engineering controls: Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations. Wear an organic vapor NIOSH/MSHA approved respirator unless local exhaust ventilation is provided or exposures are within guidelines.

Page Number: 4/7
Revision Date: 11/30/2015

Personal protective equipment: Safety glasses with side-protection, impermeable gloves (e.g., neoprene, nitrile, silver shield (R)), coveralls or apron are important in preventing contamination of eyes, skin and clothing. Wash thoroughly after handling.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Viscous liquid, aluminum sealant
Odor:	Low odor
Odor threshold:	Not available
pH (ASTM D1293):	Not available
Melting point/Freezing point:	Not available
Initial boiling point and boiling range:	Not available
Flash point:	Closed cup 108°F (42°C)
Evaporation rate:	Not available
Flammability (solid, gas):	Not available
Upper flammability or explosion limit:	Not available
Lower flammability or explosion limit:	Not available
Vapor pressure:	Not available
Vapor density:	Not available
Specific gravity:	1.01
Solubility:	Not available
Partition coefficient: n-octanol/water:	Not available
Auto-ignition temperature:	>600°F (>316°C)
Decomposition temperature:	Not available
Viscosity:	Not available
VOC:	30 grams per liter, <3% by weight (Chemically Curing Sealants and Caulks – CARB Method 310: VOC less water, less exempt compounds and LVP-VOCs).

SECTION 10 - STABILITY AND REACTIVITY

Reactivity:	Not classified as a reactivity hazard.
Chemical stability:	Stable under normal conditions.
Possibility of hazardous reactions:	Use at elevated temperatures may form highly hazardous compounds. Can react with strong oxidizing agents.
Conditions to avoid:	Moisture and incompatible materials.
Incompatible materials:	Strong oxidizing agents or electrophiles (e.g. ferric chloride). Concentrated acids or bases can degrade the silicone polymer.
Hazardous decomposition products:	Carbon oxides, silicone dioxide, metal oxides, formaldehyde and traces of incompletely burned carbon products.

SB - 130 NON-FLAMMABLE METAL SEALANT

SECTION 11 - TOXICOLOGICAL INFORMATION

Page Number: 5/7
Revision Date: 11/30/2015

Information on the likely routes of exposure:

- Inhalation:** Prolonged inhalation may be harmful.
- Ingestion:** May be harmful if swallowed.
- Skin contact:** May cause skin irritation.
- Eye contact:** May cause eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics: None known

Acute toxicity:

Ingredient Name	Result	Species	Dose	Exposure
Amorphous Silica	LD50 Oral	Rat	>3,300 mg/kg	----
	LC50 Inhalation	Rat	>2.08 mg/L	4 hours
	LD50 Dermal	Rabbit	>5,000 mg/kg	----
Methyl Tri(methylethylketoxime) silane	LD50 Oral	Rat	>2,520 mg/kg	----
	LC50 Inhalation	Rat	>4.8 mg/L	4 hours
Octamethylcyclotetrasiloxane	LD50 Oral	Rat	1,540 mg/kg	----
	LC50 Inhalation	Rat	36 mg/L	4 hours
Mineral Spirits	LD50 Oral	Rat	>5,000 mg/kg	----
	LC50 Inhalation	Rat	>5,500 ppm	4 hours
	LD50 Dermal	Rabbit	>3,000 mg/kg	----

Skin corrosion/irritation: Skin irritation possible through repeated direct contact with the ketoxime in the uncured sealant.

Serious eye damage/irritation: Eye irritation possible through repeated direct contact with the ketoxime in the uncured sealant.

Aspiration hazard: No data available

Specific target organ toxicity – single exposure: Not classified based on available information.

Specific target organ toxicity – repeated exposure: Not classified based on available information.

Respiratory or skin sensitization: Allergic skin sensitization through repeated direct contact with the ketoxime in the uncured sealant.

Carcinogenicity: No ingredients considered by IARC, NTP or OSHA to be carcinogens. Male rodents exposed to Methyl Ethyl Ketoxime (CAS# 96-29-7) vapor throughout their lifetime developed liver carcinomas. These carcinomas were statistically increased at a concentration of 375 ppm.

Reproductive toxicity: Evidence of reproductive effects in laboratory animals when exposed to Octamethylcyclotetrasiloxane (CAS# 556-67-2) by inhalation at concentrations of 500 ppm or higher for 70 days prior to mating. Methyl Ethyl Ketoxime (CAS# 96-29-7) is not considered a reproductive or developmental toxin based on studies on rats.

Teratogenicity: No data available.

Germ-cell mutagenicity: Methyl Ethyl Ketoxime (CAS# 96-29-7) is not considered mutagenic or genotoxic based on in vivo and in vitro studies.

SB - 130 NON-FLAMMABLE METAL SEALANT

SECTION 12 - ECOLOGICAL INFORMATION

Page Number: 6/7
Revision Date: 11/30/2015

ECOTOXICITY:

Methyltri(methylethylketoxime)silane:

Toxicity to fish:	LC50 (Oncorhynchus mykiss (rainbow trout)): >120 mg/L, 96 hrs.
Toxicity to daphnia and other aquatic invertebrates:	EC50 (Daphnia magna (water flea)): >120 mg/L, 48 hrs.
Toxicity to algae:	ErC50 (Selenastrum capricornutum (green algae)): 94mg/L, 72 hrs.

PERSISTENCE AND DEGRADABILITY:

Methyltri(methylethylketoxime)silane:

Biodegradability: Not readily biodegradable. Biodegradation: 14.5%, 21 days.

BIOACCUMULATIVE POTENTIAL:

Methyltri(methylethylketoxime)silane:

Partition coefficient: n-octanol/water:	log Pow: 11.2
Mobility in soil:	No data available.
Other adverse effects:	No data available.

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal instructions: This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Dispose of contents/container in accordance with local, regional, national and international regulations.

Waste from residues: Dispose of in accordance with local regulations.

Contaminated packaging: Dispose of as unused product in a safe way. Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14 - TRANSPORT INFORMATION

Shipping information:

DOT PROPER SHIPPING NAME: Adhesive containing Flammable Liquid.

DOT HAZARD CLASS: UN 1133

IDENTIFICATION NO.: NMFC Item No. 149610

TDG CLASSIFICATION: Class 3.3, Packing Group III (General Exemption 1.33 for Domestic Shipments).

SECTION 15 - REGULATORY INFORMATION

SARA 304 Extremely Hazardous Substances Reportable Quantity: This product does not contain any components with a Section 304 EHS RQ.

SARA 311/312 Hazards Identification:

Fire Hazard:	Yes
Immediate (acute) Health Hazard:	Yes
Delayed (chronic) Health Hazard:	Yes
Pressure Hazard:	No
Reactivity Hazard:	No

SARA 302: No chemicals in this product are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313: This product does not contain any chemical components with known CAS No. that exceed the threshold reporting levels established by SARA Title III, Section 313.

SB - 130 NON-FLAMMABLE METAL SEALANT

State Substance List:

This product contains a listed substance(s) that appears on one or more of the Substance Lists for Pennsylvania, Massachusetts and New Jersey:

Page Number: 7/7
Revision Date: 11/30/2015

Amorphous silica (CAS# 7631-86-9)
Methyl tri(methylethylketoxime)silane (CAS# 22984-54-9)
Dimethylsiloxane, hydroxy terminated (CAS# 70131-67-8)
Dimethylsiloxane, trimethylsiloxy terminated (CAS# 63148-62-9)
Mineral spirits (CAS# 64742-88-7).

California Proposition 65:

This product does not contain any chemicals known to State of California to cause cancer, birth or any other reproductive defects.

The ingredients of this product are reported in the following inventories:

TSCA: All chemical substances in this product are included on or exempted from listing on the TSCA inventory of Chemical Substances.

DSL: All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempted from listing on the Canadian Domestic Substances List (DSL).

NFPA Profile: Health 2, Flammability 2, Reactivity 0

SECTION 16 - OTHER INFORMATION

DISCLAIMER: The information contained herein is based on data available as of the date of preparation of this SDS and which we believe to be reliable. However, no warranty is expressed or implied regarding the accuracy of the data. We shall not be responsible for the use of this information, or of any product, method or apparatus mentioned. User must make his/her own investigation to determine the suitability of the information or products for his/her particular purpose, for the protection of the environment and the health and safety of the users of this material.